Configuring for Internationalized Email Addresses (EAI)

LACRALO Universal Acceptance Training Program An LACRALO-UASG-ICANN Collaboration



Champika Wijayatunga

11 May 2021







- 1) Interpretation is available in Spanish, English and Portuguese;
 - Visit <u>www.adigo.com/icann</u> and call the number according to your country
 - Dial the channel your prefer
 - English: 9001
 - Spanish: 9003
 - Portuguese: 9007
- 2) Please mute your microphones;
- 3) Type your questions on the chat anytime and in any language or raise your hand to speak;
- 4) Have fun !



General description

Date	Session Audience		Description		
4 May 2021	Introduction to UA	General	An introduction to the fundamentals of UA and EAI.		
11 May 2021	EAI Configuration	Technical (email and system administrators)	A detailed training on how to configure email systems to support EAI.		
18 May 2021	UA for Java Developers	Technical (software developers)	A detailed training on how to design and develop applications and systems to support UA.		
25 May 2021	How to Engage in UA Activities	General	A session to discuss how participants can stay involved in UA efforts across the LAC region.		

- Certificates will be provided upon attendance and examination for modules 2 and 3.

Ð

Hello !



Champika Wijayatunga Regional Technical Engagement Manager - APAC champika.wijayatunga@icann.org



- \odot Overview of Training (5 mins)
- Introduction to EAI (20 mins)
 Quiz (5 mins)
- ⊙ Configuring for EAI (20 mins)
- EAI support by email tools and services (5 mins)
 Quiz (5 mins)
- Considerations for mailbox names using EAI (15 mins)
 Quiz (5 mins)
- Q&A (10 mins)

Introduction to Email Address Internationalization







All domain names and email addresses work in all software applications



Impact

Promote consumer choice, improve competition, and provide broader access to end users





- ⊙ Now possible to have domain names and email addresses in local languages
 - Internationalized domain names (IDNs)
 - Email Address Internationalization (EAI)
 - $\circ~$ UTF8 format by Unicode used for IDNs and EAI
- ⊙ Domain Names
 - **Newer** top-level domain names:
 - Longer top-level domain names:
 - Internationalized domain names
- Internationalized email addresses (EAI)
 - ASCII@IDN
 - UTF8@ASCII
 - UTF8@IDN
 - UTF@IDN; right to left scripts

marc@société.org ईमेल@example.com 测试@普遍接受-测试.世界 ای-میل@مثال.موقع


example.sky

example.abudhabi

普遍接受-测试.世界








Estimated Support of EAI in Email Systems Under All TLDs





Only 9.7% of the domains sampled were EAI ready in 2019

based on mail servers found through MX records in zones of All TLDs

For details on methodology, see UASG021D: EAI Readiness in TLDs



- Envelope Information that accompanies a message in transit, including the address(es) it is being sent to, and the return address to which error or failure reports can be sent
- Message Header A series of structured fields with a header name such as From: To: or Subject: followed by the contents of the header
 - free-format, such as the Subject:
 - fixed-format, such as the Date: and Message-ID:
 - A combination of fixed- and free-format, such as the To:, From: and Cc: with fixed-format addresses with free-format comment text
- Message Body The contents of a message, which may be unformatted text, or it may be one or more formatted or encoded MIME parts

EHLO mailserver.fromorg.example MAIL FROM:<sender@fromorg.example> RCPT TO:<recipient@rcptco.example>


From: sender@fromorg.example To: recipient@rcptco.example Subject: Date: other headers				
Contant Type: toyt/html:				
Content-Type: text/html;				
text MIME part				
Content-Type: application/pdf;				
attachement MIME part				

See EAI: A Technical Overview for details



- MUA Mail User Agent A client program that a person uses to send, receive, and manage mail
- MSA Mail Submission Agent A server program that receives mail from a MUA and prepares it for transmission and delivery
- MTA Mail Transmission Agent A server program that sends and receives mail to and from other Internet hosts. An MTA may receive mail from an MSA and/or deliver mail to an MDA
- MDA Mail Delivery Agent A server program that handles incoming mail and typically stores it in a mailbox or folder

These agents create and process the email envelope, message header and message body and need to be enhanced to handle Unicode text in UTF8 format to support EAI. See EAI: A Technical Overview for details






\odot What is EAI

- Having UTF8 support for:
 - mailbox name (before the @ sign)
 - domain name (after the @ sign)
- ⊙ What is not EAI
 - Having UTF8 support in:
 - Subject line
 - Address comments
 - Message body
 - MIME provides all these in conventional mail
 - Use of any character set other than UTF-8

- No EAI support only ASCII email addresses supported by the tools and services
- Level 1 can exchange email with EAI addresses
 - $\circ\,$ Receive email from an EAI address
 - $\,\circ\,$ Send email to an EAI address
 - Cannot create mailbox and domain name in UTF8
- ⊙ Level 2 Level 1 + can create EAI addresses
 - $\circ\,$ Receive email from an EAI address
 - $\circ\,$ Send email to an EAI address
 - $\circ\,$ Create mailbox and domain name in UTF8









Quiz 1



Applications present Internationalized Domain Names (IDNs) and Email Address Internationalization (EAI) to users in the following encoding format(s):

- a. ASCII
- b. UTF-8
- c. UTF-16
- d. UTF-32
- e. Some of the above





Is .ieee a valid Top Level Domain?

Configuring for EAI





- Normalize Unicode (UTF-8) string before processing, storing, etc. For IDNs use <u>NFC form</u>: e + ` (è: U+0065 U+0300) → è (U+00E8)
- Support both <u>representations of IDN labels</u>: U-label and A-label. U-Label is used for displaying and comparing; A-label for processing
 exâmple => exmple-xta => xn--exmple-xta
- Always use IDNA2008, not the older IDNA2003 version
- Do not use code/libraries that have a static list of top-level domains (TLDs) as these change often. See <u>IANA list for TLDs</u>, with regular updates
- ⊙ Do not use regex for user input validation of internationalized identifiers. Use IDNA2008 libraries for IDN; EAI local part may be difficult to validate




\odot SMTP

- $\,\circ\,$ Is augmented to support EAI
- Has a signaling flag (SMTPUTF8) to specify support of EAI
- All SMTP servers in the path must support EAI to successfully deliver the email

⊙ POP/IMAP

- Are augmented to properly support EAI
- $\,\circ\,$ Have a signaling flag to specify support of EAI








S:DATA R:354 Send your message S:From: 猫王 < 猫王@普遍接受-测试.世界> Email itself S:To: ray@receive.net S:Subject: 我们要吃午饭吗? S: S:How about lunch at 12:30? S:. R:250 Message accepted 389dck343fg34 S:QUIT R:221 Sayonara





To send and receive an email with EAI:

- All email parties involved in the delivery path have to be updated for EAI support
- If a single SMTP server in the path does not support EAI, then the email is not delivered





- What happens when one email (SMTP) server in the path does not support EAI?
 - \circ The last server trying to send to the next hop:
 - Sends back to the sender user a report of unable to deliver.
 - Drops the email
 - Similar to reports that a sender receives when an email address does not exist



• Case folding:

- In ASCII, email users expect the equivalence of lowercase and uppercase. For example, PETER@example.com and peter@example.com will be delivered to the same mailbox
- Typically for EAI, such case folding functionality is not automatically implemented in most EAI-ready software
- ⊙ SPAM:
 - EAI emails may be considered as spam by spam filtering software even when proper SPF/DKIM records are enabled

● Software/Services:

Not every server/client software and services support EAI

EAI Support by Email Tools and Services



EAI Support by Email Tools and Services



Name	MUA	MSA	MTA	MDA	MSP	Web mail
Coremail	Few	All L2	Most L2	Few	All L2	Most L2
MS Outlook.com	Most L1	Most L1	Most L1	None	None	Most L1
Yandex Mail	Few	None	None	Few	Part	Few
Roundcube	Most L2					
Apple Mail	Few					
Apple iOS Mail 14.x	Most L2					
Mozilla Thunderbird	Few					
MS Outlook	Most L1					
MS Exchange Server		All L1	All L1	Few		
Exim		Most L2	All L2			
Postfix		All L2	All L2			
Sendmail		Not tested	Not tested			
Fetchmail				Not tested		
Courier		All L2	All L2	All L2		
Gmail	All L1	All L1	All L1	Few		
XgenPlus		Not tested	Not tested	Not tested	All L2	Not tested

See detailed testing results in UASG030: Evaluation of EAI Support in Email Software and Services Report





.



Is the following statement *True* or *False*?

For Email Address Internationalization (EAI) to work all MTAs should support SMTPUTF8 signaling flag.

Quiz 4



Which of the following statement(s) are *True* when sending and receiving an email with EAI:

- a) All email parties/nodes involved in the delivery path have to be updated for EAI support
- b) If a single SMTP server in the path does not support EAI, then the email will not be delivered
- c) POP/IMAP servers could provide downgraded emails to non-EAI conforming email clients but this is not recommended
- d) None of the above

Considerations for Mailbox Names Using EAI





- Supported Scripts
 - Know user expectations for writing systems for mailbox name and domain name portion
 - Understand complexities involved for additional scripts (e.g. security, confusion, etc.)
- Length of a Mailbox Name String
 - Know constraints of your system and user expectations
 - Consider same or a similar policy as for ASCII mailbox names
- Script Mixing
 - $\circ~$ Allow limited script mixing only when clear user need based on local practice
 - Consider security and confusion due to script mixing for mailbox and domain name





- Preventing Invalid and Unstably-Rendered Strings
 - Check if <u>Reference IDN tables</u> meet desired mailbox string and update as needed
 - Use a string validation tool (e.g. <u>LGR Tool</u>) to validate the mailbox strings
- Right-to-Left (RTL) Script Consideration
 - Avoid script mixing with right-to-left scripts to avoid confusability and security issues
- Aliases and Display Names Consideration
 - Consider alias-creation option for the user interface during the mailbox name selection process. ASCII alias can be allowed with an EAI mailbox name
 - $\circ~$ Optionally allow the user to add additional aliases at a later time



\odot Signs and Symbols

- Avoid using signs and symbols, especially that do not exist on keyboard/input devices
- If required for your market, the dot (.), underscore (_), hyphen (-) and plus sign (+) are commonly used
- Review any additional signs (if needed) and ensure it does not cause a security issue
- Unicode Character Normalization
 - Understand the normalization type of your email system
 - Ensure that your email program does normalized-form-independent name comparisons
 - o If it's possible to select normalization, prefer to use NFC form



● Equivalence Considerations

- Define a policy for determining the "same" or equivalent mailbox names based on the writing system, user expectations, and technical capabilities of your implementation.
- o Examine the IDN tables, case-folding, separators, numerals, and symbols for policy
- Avoid creating different mailboxes using names which are equivalent to each other
- Share your policy to let end users understand which characters and combinations will be considered valid and which ones might have equivalence
- \odot Other considerations
 - Spell domain names with their internationalized non-ASCII names. Avoid displaying the "xn--" alternative name
 - Some email clients might not automatically link the U-label and A-label forms of email address mailbox names, so ensure that both labels are mapped to each other







Which of the following statement(s) are *False*:

- a) Universal Acceptance (UA) is the state in which all valid domain names and email addresses are accepted, validated, stored, processed, and displayed correctly and consistently
- b) To achieve Universal Acceptance, Internet applications and systems must treat all Top Level Domains (TLDs) in a consistent manner, including new generic TLDs and all internationalized TLDs
- c) All domain names should be validated against the Internationalized Domain Names in Applications IDNA2003 Standard
- d) The A-label represents a domain label in Unicode UTF8 format
- e) The A-label format is used to represent mailbox names in EAI





What is the A-label of 测试?

Hint: You can use the tool: <u>https://lgrtool.icann.org/</u>

Get Involved!





- For more information, email info@uasg.tech or UAProgram@icann.org
- Access all UA documents and presentations at website: <u>https://uasg.tech</u>

- Access details of ongoing work from wiki pages: <u>https://community.icann.org/display/TUA</u>
- Register to participate or listen in the UA discussion list at: <u>https://uasg.tech/subscribe</u>
- Register to participate in UA working groups <u>here</u>



- See <u>https://uasg.tech</u> for a complete list of reports.
 - Universal Acceptance Quick Guide: <u>UASG005</u>
 - Introduction to Universal Acceptance: <u>UASG007</u>
 - Quick Guide to EAI: UASG014
 - EAI A Technical Overview: <u>UASG012</u>
 - EAI Evaluation of Major Email Software and Services: <u>UASG021B</u>
 - Universal Acceptance Readiness Framework: <u>UASG026</u>
 - Considerations for Naming Internationalized Email Mailboxes: <u>UASG028</u>
 - Evaluation of EAI Support in Email Software and Services Report: <u>UASG030</u>

Engage with ICANN – Thank You and Questions



